

POSITION OF SECTION CORNER DETERMINED BY TIES FROM REFERENCE POINTS SET ON NOT DESCRIBED FOUND 5/8" REBAR WITH PIPELINE "RIGHT-OF-WAY" SURVEY FOR ALUM CAP SET BY OTHERS 110+42.65 AT SECTION CORNER ON PREVIOUS SURVEY. FOUND 5/8" REBAR PREVIOUS SURVEY AT 1/4 CORNER ON KINDER # MORGAN SEC 34 | SEC 35 SEC 35 | SEC 36 PREVIOUS SURVEY 1321.59 1319.34 1319.34 1321.59 SEC 2 | SEC 1 354.29 967.31 S 89°53'39" W 2638.69' SEC 3 | SEC 2 S 89°55'09" W 2643.19' LOT 4 LOT 2 LOT 1 107+19.81 SECTIONS 1, 2, & 12, TOWNSHIP 2 SOUTH, RANGE 4 WEST UINTAH SPECIAL BASE AND MERIDIAN 103+27.46 DUCHESNE COUNTY, UTAH JIMMY BROTHERSON UTE TRIBAL SN:2064-2 SECTION 2 LINE TABLE EXISTING FENCE REVISED 99+08.28 feet wide right-of-way along the left side of said described right-of-way; Commencing at the East 1/4 Corner of said Section 2; Thence South 00°18'22" West 155.43 feet to the TRUE POINT OF BEGINNING; Thence North 30°15'20" West 155.32 feet; Thence North 33°38'54" West 25.34 feet to the North line of the NE1/4 of the SE1/4 of said Section 2. Said described 91+71.05 right-of-way lines and said aliquot part line. EXISTING FENCE S 89°51'41" W 1322.69' S 89°51'41" W 1322.69' EXISTING / JIMMY BROTHERSON SN:2064 An existing 49.5 feet wide right-of-way over portions of Section 2, Township 2 South, Range 4 West of the Uintah Special 89+89.54 feet wide right-of-way along the left side of said described right-of-way; Commencing at the East 1/4 Corner of said Section 2; POINT OF BEGINNING, which is the centerline of an existing pipeline right-of-way; Thence the following ten (10) courses along said centerline; North 33°38'54" West 62.97 feet; North 34°48'55" West 253.05 feet; North 35°08'50" West 254.57 feet; $SW\frac{1}{4}$ North 35°07'55" West 345.89 feet; North 36°56'31" West 91.87 feet; $NE\frac{1}{4}$ North 34°31'44" West 164.94 feet; North 33°47'27" West 220.51 feet; $SE\frac{1}{4}$ North 21°03'21" West 51.49 feet; $NE\frac{1}{4}$ North 23°50'55" West 100.98 feet; 30' WIDE TEMPORARY RIGHT-OF-WAY NOT DESCRIBED CORRAL AND POSITION OF 1/4 CORNER An existing 49.5 feet wide right-of-way over portions of Section 2, Township 2 South, Range 4 West of the Uintah Special FOUND OLD CORNER POST AT WEST OF FOUND 5/8" REBAR QUARTER CORNER ON PREVIOUS RE-INSTALLED feet wide right-of-way along the left side of said described right-of-way; SURVEY Commencing at the Northeast Corner of said Section 2; Thence South 89°55'09" West 1321.59 feet along the North line of Lot 1 of said Section 2; S 89°53'38" W 1323.54' S 89°53'38" W 1320.34' S 89°53'38" W 1320.34' S 89°53'38" W 1323.54' 75+95.73 75+70.40 / is the centerline of an existing right-of-way; Thence the following ten (10) courses along said centerline; 72+77.48 AHEAD } EQ. STN. North 37°25'34" West 64.86 feet; North 26°57'22" West 64.73 feet; LAKE FORK RANCH INC. North 30°53'30" West 69.74 feet; SN:2066-2068 N 30.15'20" W North 18°26'18" West 57.98 feet; North 11°40'19" West 79.66 feet; North 12°22'14" West 82.21 feet; North 11°20'42" West 284.53 feet; North 09°31'32" West 107.82 feet; North 22°00'28" West 108.06 feet; $NE\frac{1}{4}$ $SE\frac{1}{4}$ TOTAL LENGTHS IN SECTION 2 LAKE FORK RANCH INC. (EXISTING PLUS 20 FEET) SN:2066 & 2068 180.66 FEET OR 10.95 RODS SN:2064 JIMMY BROTHERSON (EXISTING PLUS 20 FEET) JIMMY BROTHERSON (EXISTING PLUS 20 FEET) SCALE: 1"=300" BASIS OF BEARINGS PUBLIC LAND SURVEY SYSTEM SECTION CORNER PUBLIC LAND SURVEY SYSTEM 1/4 CORNER SURVEYOR'S CERTIFICATE I, D. RYAN ALLRED, DUCHESNE COUNTY, UTAH, DO HEREBY CERTIFY THAT I AM A PROFESSIONAL LAND SURVEYOR AND THAT I SECTION LINE --- INTERIOR SECTION LINE $SE\frac{1}{4}$ ------ PROPERTY LINE $SE\frac{1}{4}$ -x - x - x - x - x - x - FENCE LINE- OHP - OHP - OHP - OHP - OVERHEAD POWER POWER POLE SECTION CORNER SEARCHED FOR AND NOT FOUND. POSITION FALLS IN RIVER FLOOD PLAIN WITH SIGNS OF BEING INUNDATED DURING FLOOD PERIODS. POSITION OF FOUND COUNTY MONUMENT FOUND DUCHESNE COUNTY MONUMENT CORNER DETERMINED BY DOUBLE AT SECTION CORNER ON PROPORTION MEASURE ON PREVIOUS PREVIOUS SURVEY AT 1/4 CORNER ON PREVIOUS SURVEY SEC 2 SEC 1 SEC 3 SEC 2 SEC 11 \ SEC 12 SEC 10 | SEC 11 N 89°59'20" W 2638.18' S 89°54'40" W 2638.63' REV 28 FEB 2017 REV 18 FEB 2017

RAVOLA DISCHARGE LINE UPGRADE

SECTION 35, TOWNSHIP 1 SOUTH, RANGE 4 WEST

RIGHT-OF-WAY DESCRIPTION -- EXISTING PLUS 20 FEET (LAKE FORK RANCH INC. SN:2066 & 2068)

An existing 49.5 feet wide right-of-way over portions of Section 2, Township 2 South, Range 4 West of the Uintah Special Base and Meridian, the width being 24.75 feet on either side of the following described centerline, with an additional 20

right-of-way being 180.66 feet in length, with the sidelines being shortened or elongated to intersect existing

RIGHT-OF-WAY DESCRIPTION -- EXISTING PLUS 20 FEET (JIMMY BROTHERSON SN:2064)

Base and Meridian, the width being 24.75 feet on either side of the following described centerline, with an additional 20

Thence South 89°53'38" West 93.13 feet along the South line of the SE/14 of the NE1/4 of said Section 2 to the TRUE

North 26°20'36" West 29.04 feet to the South line of Lot 1 of said Section 2. Said described right-of-way being 1575.32 feet in length, with the sidelines being shortened or elongated to intersect existing right-of-way lines and said

RIGHT-OF-WAY DESCRIPTION -- EXISTING PLUS 20 FEET (JIMMY BROTHERSON SN:2064-2)

Base and Meridian, the width being 24.75 feet on either side of the following described centerline, with an additional 20

Thence South 00°05'09" West 1029.50 feet along the West line of said Lot 1 to the the TRUE POINT OF BEGINNING, which

North 26°54'52" West 180.72 feet to the North line of Lot 2 of said Section 2. Said described right-of-way being 1100.31 feet in length, with the sidelines being shortened or elongated to intersect said Lot lines.

1575.32 FEET OR 95.47 RODS 1100.31 FEET OR 66.69 RODS

THE BASIS OF BEARINGS IS GEODETIC NORTH DERIVED FROM G.P.S. OBSERVATIONS AT A 1/4 CORNER LOCATED AT LAT. 40°21'07.6999"N AND LONG. 110°16'30.8142"W USING THE UTAH STATE G.P.S. VIRTUAL REFERENCE STATION CONTROL NETWORK MAINTAINED AND OPERATED BY THE AUTOMATED GEOGRAPHIC REFERENCE CENTER

HOLD CERTIFICATE NUMBER 376084 AS PRESCRIBED BY THE STATE OF UTAH. I FURTHER CERTIFY THAT THIS PLAT WAS PREPARED FROM THE FIELD NOTES AND ELECTRONIC DATA COLLECTOR FILES OF AN ACTUAL SURVEY MADE BY ME OR UNDER MY PERSONAL SUPERVISION AND THAT THE MONUMENTS INDICATED WERE FOUND OR SET DURING SAID SURVEY, AND THAT THIS PLAT ACCURATELY REPRESENTS SAID SURVEY TO THE BEST OF MY KNOWLEDGE AND BELIEF.



COUNTY SURVEYOR FILE NO. 4208 3 44 JERRY D. ALLRED & ASSOCIATES, INC. 235 NORTH 700 EAST--P.O. BOX 975 DUCHESNE, UTAH 84021

(435) 738-5352

14 FEB 2017 12-121-374

SEC 26 SEC 25 SEC 27 SEC 26 SEC 35 | SEC 36 S 89°29'49" W 2640.16' S 89°26'46" W 1317.76' S 89°37'31" W 1317.36' SEC 34 | SEC 35 FOUND MON SPIKE FOUND MON SPIKE AT SECTION CORNER FOUND 5/8" REBAR AT 1/4 CORNER AT 1/16 CORNER AS PER FOUND 5/8" REBAR COUNTY TIE SHEET ON PREVIOUS SURVEY AT 1/16 CORNER AS PER COUNTY TIE SHEET SCALE: 1"=300' **LEGEND** S 89°43'03" E 1303.52' PUBLIC LAND SURVEY SYSTEM SECTION CORNER SET MAG SPIKE AND FOUND 5/8" REBAR IN A MOUND OF STONES UNDER AN WASHER AT 1/16 CORNER PUBLIC LAND SURVEY SYSTEM 1/4 CORNER D00 EAST-WEST FENCE LINE AT ON PREVIOUS SURVEY ON 1/16 CORNER ON PREVIOUS PREVIOUS SURVEY ----- SECTION LINE --- -- INTERIOR SECTION LINE EXISTING 3 ROD R/W PROPERTY LINE $- \times - \times - \times - \times - \times - FENCE$ LINE SE1/4- OHP - OHP - OHP - OHP - OHP - OVERHEAD POWER NW1/4POWER POLE LAUNCHER/RECEIVER JIMMY BROTHERSON 142+55.16 SN:1039 THE RIGHT-OF-WAY FROM STATION 139+02.02 TO STATION PERMANENT RIGHT-OF-WAY-44.75' 142+55.16 IS TO REPLACE THE PERMANENT RIGHT-OF-WAY-EXISTING RIGHT-OF-WAY FOR SAID LOCATION ONLY IRRIGATION DITCH PIPELINE FOUND COUNTY TO BE RELOCATED 139+02.02 MONUMENT AT N 89°09'03" E 1336.01' N 89°09'03" E 1336.01' 1/4 CORNER S 89°42'52" E 1306.77' S 89°42'52" E 1306.77' NO SEARCH MADE FOUND SPIKE NAIL 0.10' 1232.52' FOR 1/4 CORNER UNDER SURFACE OF ROAD AT C LINE TABLE 1/4 CORNER ON PREVIOUS SURVEY 5 70.33'55" E 135+98.45 EXISTING 6 NE1/4PIPELINE SW1/4133+28.25 131 + 28.14NW1/4SE1/4MARTIN BROTHERSON TRIBAL SN:1037 SN:NONE L61 N 00°14'14" E 13' OF NEW R/W N 89°48'33" E 1320.90' N 89°48'33" E 1320.90' N 89°48'33" E 1320.90' N 89°48'33" E 1320.90' JIMMY BROTHERSON SE1/4SE1/4SW1/430' WIDE TEMPORARY RIGHT-OF-WAY NOT DESCRIBED POSITION OF SECTION CORNER FOUND 5/8" REBAR WITH ALUM CAP SET BY OTHERS DETERMINED BY TIES FROM REFERENCE POINTS SET ON AT SECTION CORNER ON PREVIOUS SURVEY. FOUND 5/8" REBAR PREVIOUS SURVEY AT 1/4 CORNER ON SEC 34 | SEC 35 SEC 35 SEC 36 PREVIOUS SURVEY 1321.59 1319.34 SEC 1 354.29 S 89°53'39" W 2638.69' S 89°55'09" W 2643.19' SEC 3 | SEC 2

PIPELINE "RIGHT-OF-WAY" SURVEY FOR

KINDER # MORGAN

RAVOLA DISCHARGE LINE UPGRADE

SECTION 35, TOWNSHIP 1 SOUTH, RANGE 4 WEST

SECTIONS 1, 2, & 12, TOWNSHIP 2 SOUTH, RANGE 4 WEST UINTAH SPECIAL BASE AND MERIDIAN DUCHESNE COUNTY, UTAH

> SECTION 35 REVISED

RIGHT-OF-WAY DESCRIPTION -- EXISTING PLUS 20 FEET (JIMMY BROTHERSON SN:1036) An existing 49.5 feet wide right-of-way over portions of Section 35, Township 1 South, Range 4 West of the Uintah Special Base and Meridian, the width being 24.75 feet on either side of the following described centerline, with an additional 20 feet wide right-of-way along the left side of said described right-of-way; Commencing at the South 1/4 Corner of said Section 35;

Thence North 89°55'09" East 967.31 feet along the South line of the SW1/4 of the SE1/4 of said Section 35 to the TRUE POINT OF BEGINNING, which is the centerline of an existing pipeline;

Thence along said centerline the following nine (9) courses; North 26°54'52" West 34.07 feet;

North 29°06'00" West 301.93 feet; North 29°31'27" West 80.00 feet;

North 30°43'53" West 172.40 feet;

North 30°54'00" West 310.18 feet; North 29°25'19" West 128.46 feet;

North 30°31'47" West 163.28 feet;

North 30°39'24" West 264.60 feet;

North 31°24'17" West 64.85 feet to the North line of said aliquot part. Said described right-of-way being 1519.77 feet in length, with the sidelines being shortened or elongated to intersect existing aliquot part lines.

RIGHT-OF-WAY DESCRIPTION -- EXISTING PLUS 20 FEET (MARTIN BROTHERSON SN:1037)

An existing 49.5 feet wide right-of-way over portions of Section 35, Township 1 South, Range 4 West of the Uintah Special Base and Meridian, the width being 24.75 feet on either side of the following described centerline, with an additional 20 feet wide right-of-way along the left side of said described right-of-way; Commencing at the West 1/4 Corner of said Section 35;

Thence South 70°33'55" East 2799.72 feet to the TRUE POINT OF BEGINNING, which is the centerline of an existing pipeline

Thence along said centerline the following eight (8) courses; North 32°40'00" West 46.49 feet;

North 31°56'29" West 84.11 feet; North 27°44'59" West 39.09 feet;

North 00°11'11" West 200.11 feet;

North 02°09'59" East 131.64 feet;

North 00°14'14" East 138.57 feet; North 01°11'16" West 237.23 feet;

North 00°28'58" West 66.34 feet to the center section line. Said described right-of-way being 943.57 feet in length, with the sidelines being shortened or elongated to intersect said section lines.

RIGHT-OF-WAY DESCRIPTION -- TO REPLACE EXISTING (JIMMY BROTHERSON SN:1039)

A 69.5 feet wide right-of-way over portions of Section 35, Township 1 South, Range 4 West of the Uintah Special Base and Meridian, the width being 24.75 feet on the right side and 44.75 feet on the left side of the following described

Commencing at the West 1/4 Corner of said Section 35;

Thence South 89°42'58" East 2539.29 feet along the center section line of said Section 35 to the TRUE POINT OF

Thence North 00°20'09" East 353.14 feet to the point of terminus. Said described right-of-way being 353.14 feet in length, with the sidelines being shortened or elongated to intersect said center section line and being perpendicular to

TOTAL LENGTHS IN SECTION 35

1519.77 FEET OR 92.11 RODS SN:1036 JIMMY BROTHERSON (EXISTING PLUS 20 FEET) 943.57 FEET OR 57.19 RODS SN:1037 MARTIN BROTHERSON (EXISTING PLUS 20 FEET) JIMMY BROTHERSON (NEW 69.5 FEET WIDE REPLACE PREVIOUS) SN:1039 353.14 FEET OR 21.40 RODS

BASIS OF BEARINGS


THE BASIS OF BEARINGS IS GEODETIC NORTH DERIVED FROM G.P.S. OBSERVATIONS AT A 1/4 CORNER LOCATED AT LAT. 40°21'07.6999"N AND LONG. 110°16'30.8142"W USING THE UTAH STATE G.P.S. VIRTUAL REFERENCE STATION CONTROL NETWORK MAINTAINED AND OPERATED BY THE AUTOMATED GEOGRAPHIC REFERENCE CENTER

SURVEYOR'S CERTIFICATE

REV 28 FEB 2017

14 FEB 2017 12-121-374

I, D. RYAN ALLRED, DUCHESNE COUNTY, UTAH, DO HEREBY CERTIFY THAT I AM A PROFESSIONAL LAND SURVEYOR AND THAT I HOLD CERTIFICATE NUMBER 376084 AS PRESCRIBED BY THE STATE OF UTAH. I FURTHER CERTIFY THAT THIS PLAT WAS PREPARED FROM THE FIELD NOTES AND ELECTRONIC DATA COLLECTOR FILES OF AN ACTUAL SURVEY MADE BY ME OR UNDER MY PERSONAL SUPERVISION AND THAT THE MONUMENTS INDICATED WERE FOUND OR SET DURING SAID SURVEY, AND THAT



COUNTY SURVEYOR FILE NO. 4208-464

JERRY D. ALLRED & ASSOCIATES, INC. SURVEYING CONSULTANTS 1235 NORTH 700 EAST--P.O. BOX 975 DUCHESNE, UTAH 84021 (435) 738-5352